



Art.-Nr: AIW009-E

Exit sign Centralised power supply systems

Wall mounting, Without monitoring, CPS, 15 m, IP40, Zinc die-cast, Stainless steel

Modern zinc die-cast emergency exit sign luminaire for surface mounting on the wall and for identifying emergency and escape routes.

It is part of the A series luminaire family, which provides solutions for any mounting and has won the German Design Award for its uniform, straight-line design.

The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.



More information

www.rp-group.com/en/item/AIW009-E



TECHNICAL DATA

| | |
|------------------------|----------------------------------|
| Luminaire type | Exit sign |
| Mounting | Wall mounting |
| Recognition distance | 15 m |
| Pictograph | Set |
| Illuminant | LED |
| Housing material | Zinc die-cast |
| Housing color | Stainless steel |
| Protection type (IP) | IP40 |
| Impact resistance (IK) | ≥ 3 |
| Certification | CE, WEEE |
| Insulation class | 2 |
| Supply | Centralised power supply systems |
| Monitoring | Without monitoring |
| Bridging time | CPS |
| Battery | / |



| | |
|----------------------------------|---------------------|
| Operating mode | Permanent circuit |
| Input voltage AC | 230 V |
| Input frequency | 50 / 60 Hz |
| Input voltage DC | 100-254 V |
| Power max. | 1,7 W |
| Power DS | 1,7 W |
| Power BS | 0 W |
| Ambient temperature DS | -5 °C - 40 °C |
| Ambient temperature BS | -5 °C - 40 °C |
| Depth | 55 mm |
| Width | 193 mm |
| Height | 120 mm |
| Installation dimensions Diameter | 68 mm |
| Weight | 1.04 |
| Weight incl. packaging | 1.29 |
| Connection cross-section | 1.5 mm ² |
| Switching input | No |
| Emergency light blocking | No |
| Battery connection | No |
| Dimming function | No |
| Customs tariff number | 94056180 |
| EAN | 4260682152435 |



TECHNICAL DRAWING



As of: 11.10.2024 - Subject to technical changes and errors.