



**Art.-Nr: AMR009ML-E**  
**Exit sign Central power supply**  
**Recessed wall mounting, ML, Central power supply, 22 m,**  
**IP40, Zinc die-cast, Stainless steel**

The AMR is a zinc-diecast exit sign for recessed wall mounting and for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaires of the A-Series are equipped with modern LED illuminants and offer flexibility with changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838



[More information](#)



## TECHNICAL DATA

|                        |                            |
|------------------------|----------------------------|
| Luminaire type         | Exit sign                  |
| Mounting               | Recessed wall mounting     |
| Recognition distance   | 22 m                       |
| Pictograph             | Set                        |
| Illuminant             | LED                        |
| Housing material       | Zinc die-cast              |
| Housing color          | Stainless steel            |
| Protection type (IP)   | IP40                       |
| Impact resistance (IK) | ≥ 3                        |
| Certification          | Waste disposal, CE, ENEC   |
| Insulation class       | 2                          |
| Supply                 | Central power supply       |
| Monitoring             | ML                         |
| Bridging time          | Central power supply       |
| Operating mode         | single luminaire switching |
| Input voltage AC       | 230 V                      |
| Input frequency        | 50 / 60 Hz                 |
| Input voltage DC       | 216 V                      |
| Power max.             | 3,5 W                      |
| Power DS               | 3,5 W                      |



|                          |                     |
|--------------------------|---------------------|
| Power BS                 | 1,1 W               |
| Depth                    | 79 mm               |
| Width                    | 236 mm              |
| Height                   | 151 mm              |
| Installation length      | 176 mm              |
| Installation width       | 68 mm               |
| Installation height      | 40 mm               |
| Weight                   | 1.02                |
| Weight incl. packaging   | 1.38                |
| Connection cross-section | 2.5 mm <sup>2</sup> |
| Switching input          | Yes                 |
| Emergency light blocking | No                  |
| Battery connection       | No                  |
| Dimming function         | Yes                 |
| Customs tariff number    | 94056180            |
| Country of origin        | DEUTSCHLAND         |
| EAN                      | 4260581714611       |



## TECHNICAL DRAWING



## ACCESSORY LIST

BALLPLX-AM -

AM-XBE -



## RELATED PRODUCTS

| Art.-No.    | Image | Monitoring     | Supply               | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|-------------|-------|----------------|----------------------|-------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| AMR009ML    |       | ML             | Central power supply |       | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| AMR009ML-AZ |       | ML             | Central power supply |       | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| AMR509CC    |       | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |
| AMR509CC-AZ |       | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |
| AMR509CC-E  |       | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |

As of: 27.06.2024 - Subject to technical changes and errors.