



**Art.-Nr: AXCC009ML-E**

**Exit sign Central power supply**

**Ceiling mounting, ML, Central power supply, 30 m, IP20, Zinc die-cast, Stainless steel**

The AXCC is a zinc-diecast exit sign with cord suspension for recessed ceiling mounting for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaire of the A-Series are of course equipped with modern LED illuminants and offer the flexibility of changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838



[More information](#)



## TECHNICAL DATA

|                      |                            |
|----------------------|----------------------------|
| Luminaire type       | Exit sign                  |
| Mounting             | Ceiling mounting           |
| Recognition distance | 30 m                       |
| Pictograph           | Set                        |
| Illuminant           | LED                        |
| Housing material     | Zinc die-cast              |
| Housing color        | Stainless steel            |
| Protection type (IP) | IP20                       |
| Certification        | Waste disposal, CE, ENEC   |
| Insulation class     | 2                          |
| Supply               | Central power supply       |
| Monitoring           | ML                         |
| Bridging time        | Central power supply       |
| Operating mode       | single luminaire switching |
| Input voltageAC      | 230 V                      |
| Input frequency      | 50 / 60 Hz                 |
| Input voltage DC     | 216 V                      |
| Power max.           | 4,5 W                      |
| Power DS             | 4,5 W                      |
| Power BS             | 1,1 W                      |



|                          |                     |
|--------------------------|---------------------|
| Depth                    | 80 mm               |
| Width                    | 312 mm              |
| Height                   | 181 mm              |
| Installation length      | 176 mm              |
| Installation width       | 68 mm               |
| Installation height      | 40 mm               |
| Weight                   | 1.9                 |
| Weight incl. packaging   | 2.39                |
| Connection cross-section | 2.5 mm <sup>2</sup> |
| Switching input          | Yes                 |
| Emergency light blocking | No                  |
| Battery connection       | No                  |
| Dimming function         | Yes                 |
| Customs tariff number    | 94056180            |
| Country of origin        | DEUTSCHLAND         |
| EAN                      | 4260581715144       |



## TECHNICAL DRAWING



## ACCESSORY LIST

AM-XBE -



## RELATED PRODUCTS

| Art.-No.     | Image                                                                               | Monitoring     | Supply               | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|--------------|-------------------------------------------------------------------------------------|----------------|----------------------|-------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| AXCC009ML    |    | ML             | Central power supply |       | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| AXCC009ML-AZ |   | ML             | Central power supply |       | €€€        | Yes           | low               | Yes                | 1,920 per system | central                     |
| AXCC509CC    |  | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |
| AXCC509CC-AZ |  | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |
| AXCC509CC-E  |  | CoreCompact 24 | Central power supply |       | €€         | Yes           | low               | Yes                |                  | central                     |

As of: 27.06.2024 - Subject to technical changes and errors.