



**Art.-Nr: AXCC408WL-E**  
**Exit sign Single Battery**  
**Ceiling mounting, Wireless Professional, 8 h, 30 m, IP20, Zinc die-cast, Stainless steel**

The AXCC is a zinc-diecast exit sign with cord suspension for recessed ceiling mounting for the marking of escape routes. It is part of a complete luminaire series, which features solutions for every mounting situation and was honored with the German Design Award. Luminaire of the A-Series are of course equipped with modern LED illuminants and offer the flexibility of changeable pictograms.

LED exit sign according to EN 60598-1, EN 60598-2-22, EN 7010 and EN 1838



More information



## TECHNICAL DATA

|                      |  |
|----------------------|--|
| Luminaire type       | Exit sign  |
| Mounting             | Ceiling mounting   |
| Recognition distance | 30 m   |
| Pictograph           | Set  |
| Illuminant           | LED  |
| Housing material     | Zinc die-cast  |
| Housing color        | Stainless steel  |
| Protection type (IP) | IP20   |
| Certification        | WEEE, CE, ENEC   |
| Insulation class     | 2  |
| Supply               | Single Battery   |
| Monitoring           | Wireless Professional  |
| Bridging time        | 8 h  |
| Battery              | LiFePO4 - 2 pcs - 3,2 V / 1200mAh LiFePO4 - Lithium Iron Phosphate Battery |
| Operating mode       | Standby circuit / permanent circuit  |
| Input voltageAC      | 230 V  |
| Input frequency      | 50 Hz  |
| Power max.           | 5,6 W  |
| Power DS             | 4,5 W  |
| Power BS             | 0,8 W  |



|                          |                     |
|--------------------------|---------------------|
| Depth                    | 80 mm               |
| Width                    | 312 mm              |
| Height                   | 181 mm              |
| Installation length      | 176 mm              |
| Installation width       | 68 mm               |
| Installation height      | 40 mm               |
| Weight                   | 2.05                |
| Weight incl. packaging   | 2.54                |
| Connection cross-section | 2.5 mm <sup>2</sup> |
| Switching input          | Yes                 |
| Emergency light blocking | Yes                 |
| Battery connection       | Connector           |
| Dimming function         | Yes                 |
| Customs tariff number    | 94056180            |
| Country of origin        | DEUTSCHLAND         |
| EAN                      | 4260682154880       |



## TECHNICAL DRAWING



## ACCESSORY LIST

AM-XBE -  
LFP3212-LEO - Technology Battery



## RELATED PRODUCTS

| Art.-No.     | Image | Monitoring            | Supply         | Color | Investment | Automatic log | Maintenance level | Remote maintenance | max. luminaires  | Single luminaire monitoring |
|--------------|-------|-----------------------|----------------|-------|------------|---------------|-------------------|--------------------|------------------|-----------------------------|
| AXCC408WL    |       | Wireless Professional | Single battery |       | €€         | yes           | low               | yes                | 1,000 per system | central                     |
| AXCC408WL-AZ |       | Wireless Professional | Single battery |       | €€         | yes           | low               | yes                | 1,000 per system | central                     |

As of: 08.07.2024 - Subject to technical changes and errors.