



Art.-Nr: FMDS423SC-AZ
Safety luminaire
Recessed mounting, SelfControl (SC), 3 h, , IP65, Zinc die-cast, Anthracite

Robust zinc die-cast safety luminaire for mounting on the ceiling and for illuminating escape and emergency routes.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/FMDS423SC-AZ




TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Recessed mounting
Pictograph	No
Housing material	Zinc die-cast
Housing color	Anthracite
Protection type (IP)	IP65
Impact resistance (IK)	8
Certification	WEEE, CE, D-Sign
Insulation class	1
Monitoring	SelfControl (SC)
Bridging time	3 h
Battery	LiFePO4 6,4 V/3,3Ah Ah
Power max.	7,3 W
Power DS	5,9 W
Power BS	0,9 W
Ambient temperature DS	-5 °C to 40 °C
Ambient temperature BS	-5 °C to 40 °C
Depth	58 mm
Width	262 mm
Height	188 mm
Weight	2.12



Weight incl. packaging	2.22
Luminous flux mains	520 lm
Luminous flux emergency	520 lm
Customs tariff number	94056180
EAN	4260766556081

TECHNICAL DRAWING



ACCESSORY LIST

FMDA001-AZ -
FMDA002-AZ -
FMWA001 -
FMFH -

As of: 06.03.2025 - Subject to technical changes and errors.