



## Art.-Nr: FMW403WL-AZ **Exit sign Single Battery** Wall mounting, Wireless Professional (WL), 3 h, 20 m, IP65, Zinc die-cast, Anthracite

Robust zinc die-cast emergency exit sign luminaire for mounting on the wall and for identifying emergency and escape routes.

The pictogram is fitted on the inside where it is protected by a transparent pane.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.









www.rp-group.com/en/item/FMW403WL-



## **TECHNICAL DATA**

| Luminaire type         | Exit sign                           |
|------------------------|-------------------------------------|
| Mounting               | Wall mounting                       |
| Recognition distance   | 20 m                                |
| Pictograph             | Set                                 |
| Illuminant             | LED                                 |
| Housing material       | Zinc die-cast                       |
| Housing color          | Anthracite                          |
| Protection type (IP)   | IP65                                |
| Impact resistance (IK) | 8                                   |
| Certification          | WEEE, CE, D-Sign                    |
| Insulation class       | 1                                   |
| Supply                 | Single Battery                      |
| Monitoring             | Wireless Professional (WL)          |
| Bridging time          | 3 h                                 |
| Battery                | LiFePO4 6,4 V/1,2 Ah                |
| Operating mode         | Standby circuit / permanent circuit |







| Input voltageAC          | 230 V         |
|--------------------------|---------------|
| Input frequency          | 50 Hz         |
| Power max.               | 3,9 W         |
| Power DS                 | 2,6 W         |
| Power BS                 | 0,8 W         |
| Ambient temperature DS   | -5 °C - 40 °C |
| Ambient temperature BS   | -5 °C - 40 °C |
| Depth                    | 58 mm         |
| Width                    | 262 mm        |
| Height                   | 188 mm        |
| Weight                   | 2.11          |
| Weight incl. packaging   | 2.21          |
| Connection cross-section | 2.5 mm²       |
| Switching input          | Yes           |
| Emergency light blocking | Yes           |
| Battery connection       | Connector     |
| Dimming function         | Yes           |
| Customs tariff number    | 94056180      |
| EAN                      | 4260766557255 |






## TECHNICAL DRAWING









## **ACCESSORY LIST**

FMWA001 -

FMDA001 -

FMDA002-AZ -

FMFH -

FMDA001-AZ -

FMDA002 -

As of: 11.10.2024 - Subject to technical changes and errors.