



### Art.-Nr: FMWT009ML **Exit sign Centralised power supply systems** Wall mounting, Central power supply (ML), CPS, 20 m, IP65, Zinc die-cast, white

Robust zinc die-cast emergency exit sign luminaire for mounting on the wall and for identifying emergency and escape routes.

The pictogram is fitted on the inside where it is protected by a transparent pane.

The additional LED, which is operated in duo technology, illuminates the escape and rescue routes in case of a power failure.

Control and monitoring via central power supply system. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.







More information www.rp-group.com/en/item/FMWT009ML



#### **TECHNICAL DATA**

Luminaire type	Exit sign				
Mounting	Wall mounting				
Recognition distance	20 m				
Pictograph	Set				
Housing material	Zinc die-cast				
Housing color	white				
Protection type (IP)	IP65				
Impact resistance (IK)	8				
Certification	WEEE, CE, D-Sign				
Insulation class	1				
Supply	Centralised power supply systems				
Monitoring	Central power supply (ML)				
Bridging time	CPS				
Battery	/				
Operating mode	single luminaire switching				







Input voltageAC	230 V				
Input frequency	50 / 60 Hz				
Input voltage DC	216 V				
Power max.	3,9 W				
Power DS	2,9 W				
Power BS	1,1 W				
Ambient temperature DS	-20 °C - 40 °C				
Ambient temperature BS	-20 °C - 40 °C				
Depth	58 mm				
Width	262 mm				
Height	188 mm				
Weight	1.96				
Weight incl. packaging	2.06				
Connection cross-section	2.5 mm <sup>2</sup>				
Switching input	Yes				
Emergency light blocking	No				
Battery connection	No				
Dimming function	Yes				
Luminous flux emergency	100 lm				
Customs tariff number	94056180				
EAN	4260581717735				






## **TECHNICAL DRAWING**









#### **ACCESSORY LIST**

FMWA001 -

FMDA001 -

FMDA002-AZ -

FMFH -

FMDA001-AZ -

FMDA002 -

# RELATED PRODUCTS

ArtNo		lmage	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single luminai- re monitoring
FMWT0	009ML-	<b>**</b>	Central power supply (ML)	Central power supply	RAL 7016	€€€	Yes	low	Yes	1,920 per system	central

As of: 11.10.2024 - Subject to technical changes and errors.