


Art.-Nr: KAXU403WL

Cuboid polycarbonate luminaire design, discreetly reduced to the essentials. The design and universal installation is based on the KB luminaire, whereby the edge for holding the escape sign is permanently installed. The luminaires are equipped with modern LED lighting devices and offer flexibility through interchangeable pictograms. The high degree of protection enables use in damp rooms or environments with high levels of soiling.







Technical Data

Luminaire type Exit sign Mounting Universal Recognition distance 30 m Pictograph Set LED Illuminant Housing material Plastic Housing color white **IP64** Protection type (IP) Impact resistance (IK) 7

Certification CE, WEEE

Insulation class 2

Supply Single Battery

Monitoring Wireless Professional

Bridging time 3 h

Battery LiFePO4 - 2 pcs - 3,2 V /1200mAh LiFePO4 - Lithium Iron Phosphate Battery

Operating mode Standby circuit / permanent circuit

Input voltageAC	230 V
Input frequency	50 Hz
Power max.	5,6 W
Power DS	4,5 W
Power BS	0,8 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C
Depth	326 mm
Width	50 mm
Height	248 mm
Weight	0.23
Weight incl. packaging	0.43

Weight 0.23
Weight incl. packaging 0.43
Connection cross-section 2.5 mm²
Switching input Yes
Emergency light blocking Yes

Battery connection Connector

Dimming function Yes

Customs tariff number 94056120

EAN 4260766551635

Technical drawing

