




Art.-Nr: KBU413SC-IP65-COOLIP54

Exit sign, Safety luminaire

Universal, SelfControl, 3 h, 14 m, 22 m, 30 m, IP64, Plastic, white

LED exit sign / emergency light according to DIN EN 60598-1, EN 60598-2-22, EN 7010 and DIN EN 1838.

Cuboid plastic housing design reduced on the lamps substance. Modular design and universal mounting for use as emergency luminaire with and without the application of pictograms. The modular system allows the luminaire to be converted to an exit sign luminaire at any time without dismantling or tools. Panes for mounting pictographs have to be ordered seperately.



[More information](#)





TECHNICAL DATA

Luminaire type	Exit sign, Safety luminaire
Mounting	Universal
Recognition distance	14 m, 22 m, 30 m
Pictograph	acc. to Specification
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP64
Impact resistance (IK)	5
Certification	WEEE, TÜV Rheinland Type approved, CE, ENEC
Insulation class	2
Monitoring	SelfControl
Bridging time	3 h
Power max.	4,1 W
Power DS	3,3 W
Power BS	0,4 W
Ambient temperature DS	-5 °C - 35 °C
Ambient temperature BS	-5 °C - 40 °C
Depth	326 mm
Width	50 mm



Height	50 mm
Weight	0.4
Weight incl. packaging	0.45
Luminous flux mains	225 lm
Luminous flux emergency	225 lm
Customs tariff number	94056120
EAN	4262483021064

TECHNICAL DRAWING



ACCESSORY LIST

KBK -
KBM -
KBG -
AWX001 -
KBE -
BALLPLX-KBE -
BALLPLX-KBS -
BALLPLX-KBU -
2PW-EB -
2DW-EB -
KBBE -
DSA -

As of: 10.07.2024 - Subject to technical changes and errors.