



Art.-Nr: KCD418WL **Exit sign Single Battery** Recessed mounting, Wireless Professional (WL), 8 h, 30 m, IP40, Plastic, white

Slim convex plastic emergency exit sign luminaire for ceiling mounting. Suited to inscription on one or two sides. The plug-in set of pictograms is fitted on the inside without the use of solvents.

Wireless central control and monitoring for large installations of up to 50,000 luminaires with Wireless Professional. The innovative integrated lens holder with a rapid fitting fixture permits the flexible use of various lens types. Using the right lens allows the distribution of light to be matched perfectly to the application and simplifies illumination which satisfies all relevant standards. A round lens and hall lens are supplied with every luminaire, allowing it to be adapted perfectly to the respective mounting situation. Other lenses, such as a spotlight lens, beam lens or H lens, are available as options.







More information www.rp-group.com/en/item/KCD418WL



TECHNICAL DATA

Luminaire type	Exit sign				
Mounting	Recessed mounting				
Recognition distance	30 m				
Pictograph	Set				
Illuminant	LED				
Housing material	Plastic				
Housing color	white				
Protection type (IP)	IP40				
Impact resistance (IK)	≥ 3				
Certification	WEEE, CE, D-Sign				
Insulation class	1				
Supply	Single Battery				
Monitoring	Wireless Professional (WL)				
Bridging time	8 h				
Battery	LiFePO4 6,4 V/3,3Ah Ah				
Operating mode	Standby circuit / permanent circuit				





Input voltageAC	230 V
Input frequency	50 Hz
Power max.	5,5 W
Power DS	3,6 W
Power BS	0,7 W
Ambient temperature DS	-5 °C - 40 °C
Ambient temperature BS	-5 °C - 40 °C
Depth	90 mm
Width	340 mm
Height	170 mm
Weight	1.09
Weight incl. packaging	1.2
Connection cross-section	2.5 mm²
Switching input	Yes
Emergency light blocking	Yes
Battery connection	Connector
Dimming function	Yes
Customs tariff number	94056120
EAN	4260766552151






TECHNICAL DRAWING











ACCESSORY LIST

KCAWW - Wall bracket

DSA - Wire suspension

2PW-EB - Pendant

WKL - Eye bolts

RELATED PRODUCTS

level tenance res re monitor	ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote main- tenance	max. luminai- res	Single lumina
------------------------------	--------	-------	------------	--------	-------	------------	---------------	----------------------	-------------------------	----------------------	---------------

As of: 11.10.2024 - Subject to technical changes and errors.