



Art.-Nr: KSC019-SW

Exit sign, Safety luminaire Centralised power supply systems Universal, CPS, CPS, 22 m, IP54, Plastic, Black

Innovative high-grade LED exit sign and emergency luminare for universal mounting. This luminaire using only 3 parts has a simple installation. Applicable for maintained or non-maintained operation mode. The tolless change and variable use of the pictograms provide planning security on site. Universal pictogram set (left, right, up, down) included.

The KSC luminaire is also designed for illumination of fire fighting and first aid facilities. The equipment of the first aid facilities is lighted by at least 5 lux according to EN 1838.

Signs according to EN 60598-1, EN 60598-2-22 and EN 1838 norms.





More information



TECHNICAL DATA

Luminaire type	Exit sign, Safety luminaire
Mounting	Universal
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Plastic
Housing color	Black
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	CPS
Bridging time	CPS
Operating mode	single luminaire switching
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	216 V
Power max.	3,2 W






Power DS	3,2 W
Power BS	1 W
Depth	34 mm
Width	250 mm
Height	174 mm
Weight	0.62
Weight incl. packaging	0.7
Connection cross-section	2.5 mm²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	Yes
Luminous flux mains	220 lm
Luminous flux emergency	220 lm
Customs tariff number	94056120
Country of origin	DEUTSCHLAND
EAN	4260766550270





TECHNICAL DRAWING



ACCESSORY LIST

DSA -

AWKSU -

2PW-EB -

KMBE -

BALLPLX-KMU -

KS4FIRE -

KS4HELP -





RELATED PRODUCTS

ArtNo.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. Iuminaires	Single luminaire monitoring
KSC019ML- SW	OTIONAL STATE OF THE STATE OF T	ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KSC519CC- SW	OTIONA IN THE PROPERTY OF THE	CoreCompact 24	Central power supply		€€	Yes	low	Yes		central
KSC019ML	OTIONAL TO THE PARTY OF THE PAR	ML	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
KSC519CC	OTIONAL STATE OF THE STATE OF T	CoreCompact 24	Central power supply		€€	Yes	low	Yes		central

As of: 09.07.2024 - Subject to technical changes and errors.