



Art.-Nr: KWIW039

**Safety luminaire Centralised power supply systems
Universal, CPS, CPS, , IP65, Plastic, white**

Classic bar-shaped polycarbonate luminaire for wall or ceiling mounting. Straight lines as well as the robust construction with a high ingress protection allow versatile use.



[More information](#)




TECHNICAL DATA

Luminaire type	Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Plastic
Housing color	white
Protection type (IP)	IP65
Impact resistance (IK)	6
Certification	CE, WEEE, D-Sign
Insulation class	2
Supply	Centralised power supply systems
Monitoring	CPS
Bridging time	CPS
Operating mode	Permanent circuit
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	100-254 V
Power max.	9 W
Power DS	9 W
Power BS	0 W
Depth	86 mm
Width	390 mm
Height	99 mm



Weight	0.64
Weight incl. packaging	0.74
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	780 lm
Luminous flux emergency	780 lm
Customs tariff number	94056120
Country of origin	DEUTSCHLAND
EAN	4260659566432

TECHNICAL DRAWING





ACCESSORY LIST

BKW -

As of: 09.07.2024 - Subject to technical changes and errors.