



Art.-Nr: PFW019ML

Control and monitoring via central power supply system.



More information
www.rp-group.com/en/item/PFW019ML



TECHNICAL DATA

Illuminant	LED
Housing material	Plastic
Housing color	white
Certification	WEEE, CE, CNBOP, ENEC, D-Sign
Monitoring	Central power supply (ML)
Battery	/
Power max.	5,2 W
Power DS	5,2 W
Power BS	1,1 W
Ambient temperature DS	-20 °C - 40 °C
Ambient temperature BS	-20 °C - 40 °C
Depth	370 mm
Width	105 mm
Height	152 mm
Weight	0.95
Weight incl. packaging	1.08
Luminous flux mains	300 lm
Luminous flux emergency	300 lm
Customs tariff number	94056120
EAN	4260123683818



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
PFW019ML-P		Central power supply (ML)	Central power supply		€€€	Yes	low	Yes	1,920 per system	central
PFW519CC		CoreCompact 24 (CC)	Central power supply		€€	Yes	low	Yes		central
PFW519CC-P		CoreCompact 24 (CC)	Central power supply		€€	Yes	low	Yes		central

As of: 11.10.2024 - Subject to technical changes and errors.