



Art.-Nr: QAW403SC-SI-BM
General light, Safety luminaire Single Battery
Universal, SelfControl, 3 h, , IP20, Aluminium, white

Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. In mains operation the luminaire works with 26W / 1.600lm LED.



[More information](#)




TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminium
Housing color	white
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	1
Supply	Single Battery
Monitoring	SelfControl
Bridging time	3 h
Operating mode	Standby circuit / permanent circuit
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Power max.	30 W
Power DS	28 W
Power BS	2 W
Height	113 mm
Diameter	395 mm
Weight	0.787



Weight incl. packaging	1.107
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Connector
Dimming function	No
Luminous flux mains	2300 lm
Luminous flux emergency	360 lm
Customs tariff number	94056180
Country of origin	DEUTSCHLAND
EAN	4260682159694

TECHNICAL DRAWING



As of: 03.07.2024 - Subject to technical changes and errors.