



Art.-Nr: QAW428WL-SI
CS_VALUE_LuminaireType.Allgemeinleuchte,
CS_VALUE_LuminaireType.Sicherheitsleuchte
CS_VALUE_Supply.Einzelbatterie
CS_VALUE_MountingMethod.Universal, Wireless
Professional, CS_VALUE_BackupTime.8 h, ,
CS_VALUE_IngressProtection.IP 20, CS_VALUE_Material.34,
CS_VALUE_Color.Alu eloxiert



Round metal luminaire for general lighting and the lighting of escape and rescue routes according to DIN EN 60598-1, DIN EN 60598-2-22 and EN 1838. In mains operation the luminaire works with 26W / 1.600lm LED.



general.qrcode-more-infos



TEXT. TECHNISCHE DATEN

~pim_attribute~Leuchtentyp	CS_VALUE_LuminaireType.Allgemeinleuchte, CS_VALUE_LuminaireType.Sicherheitsleuchte
~pim_attribute~Montageart	CS_VALUE_MountingMethod.Universal
~pim_attribute~Piktogramm	CS_VALUE_LuminairePictograph.Nein
~pim_attribute~Leuchtmittel	CS_VALUE_LightSource.LED
~pim_attribute~Gehaeusematerial	CS_VALUE_Material.34
~pim_attribute~Farbe	CS_VALUE_Color.Alu eloxiert
label.zuordnungsspeicher.Schutzart	CS_VALUE_IngressProtection.IP 20
~pim_attribute~Schlagfestigkeit	CS_VALUE_IKclass.IK ≥ 3
label.zuordnungsspeicher.Zertifizierungen	CS_VALUE_Certifications.11924, CS_VALUE_Certifications.11913
~pim_attribute~Schutzklasse	CS_VALUE_InsulationClass.1
~pim_attribute~Versorgung	CS_VALUE_Supply.Einzelbatterie
~pim_attribute~Ueberwachung	Wireless Professional
~pim_attribute~Ueberbrueckungszeit	CS_VALUE_BackupTime.8 h
~pim_attribute~Batterie	LiFePO4 3,2 V / 3,3 Ah LiFePO4 - Lithium Iron Phosphate Battery
~pim_attribute~Betriebsart	CS_VALUE_OperatingMode.BS / DS
~pim_attribute~EingangsspannungAC	230 V
~pim_attribute~Eingangsfrequenz	CS_VALUE_InputFrequencyHz.50 / 60 Hz
~pim_attribute~LeistungMax	30 W



~pim_attribute~LeistungDS	26,4 W
~pim_attribute~LeistungBS	0,4 W
~pim_attribute~Hoehe	113 mm
~pim_attribute~Durchmesser	395 mm
~pim_attribute~Gewicht	0.78
label.zuordnungsspeicher.Gewicht inkl. Verpackung	1.1
~pim_attribute~Anschlussquerschnitt	2.5 mm ²
~pim_attribute~Schalteingang	CS_VALUE_SwitchInput.Ja
~pim_attribute~Notlichtblockierung	CS_VALUE_EmergencyLightBlocking.Nein
~pim_attribute~Batterieanschluss	CS_VALUE_BatteryConnection.Stecker
~pim_attribute~Dimmfunktion	CS_VALUE_DimmingFunction.Ja
~pim_attribute~LichtstromNetz	2300 lm
~pim_attribute~LichtstromNot	125 lm
~pim_attribute~Zolltarifnummer	94056180
~pim_attribute~Ursprungsland	DEUTSCHLAND
~pim_attribute~EAN	4260682159984



TEXT. TECHNICAL-DRAWINGS

