



Art.-Nr: ROPA4201SC-WW
General light, Safety luminaire Single Battery
Ceiling mounting, SelfControl, 3 h, , IP20,

The Highpower LED panel for suspended ceilings offers you the highest brightness of approx. 4,500 lm at the best price. That's about 135 lm per watt!

The cover is made of PMMA plastic and therefore UV resistant which prevents yellowing.

The Highpower LED Panel cleverly combines energy-saving general lighting with the prescribed emergency lighting.

- LED 33W
- IP20
- For 620mm grid ceilings



More information



TECHNICAL DATA

Luminaire type	General light, Safety luminaire
Mounting	Ceiling mounting
Pictograph	No
Illuminant	LED
Protection type (IP)	IP20
Impact resistance (IK)	≥ 3
Certification	Waste disposal, CE
Insulation class	2
Supply	Single Battery
Monitoring	SelfControl
Bridging time	3 h
Operating mode	Standby circuit / permanent circuit
Input voltageAC	230 V
Input frequency	50 Hz
Input voltage DC	- V
Power max.	33 W
Power DS	33 W
Power BS	2 W
Weight	0.1



Weight incl. packaging	0.18
Connection cross-section	1.5 mm ²
Switching input	Yes
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	4000 lm
Luminous flux emergency	600 lm
Customs tariff number	94056120
Country of origin	CHINA
EAN	4260682142412

As of: 03.07.2024 - Subject to technical changes and errors.