



Art.-Nr: SGS1308SC
Emergency light Self-contained
Wall mounting, SelfControl (SC), 8 h, , IP54, Metal, Light grey

Compact emergency light equipped with one freely adjustable safety illuminants mode of metal. Suitable for inside and conditionally for uotside usage. For lighting of escape and rescue routes according to EN 60598-1, EN60598-2-22 sowie EN 1838.

Automatic monitoring of safety luminaire with SelfControl.



More information
www.rp-group.com/en/item/SGS1308SC



TECHNICAL DATA

Luminaire type	Emergency light
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	Light grey
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	1
Supply	Self-contained
Monitoring	SelfControl (SC)
Bridging time	8 h
Battery	AGM - OGIV 12V 12 V/21,7 Ah
Operating mode	Non-maintained
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	12 V
Power max.	11,5 W
Power maintained	- W
Power non-maintained	9,2 W



Ambient temperature maintained mode	-5 °C to 40 °C
Ambient temperature non-maintained mode	-5 °C to 40 °C
Depth	210 mm
Width	400 mm
Height	300 mm
Weight	22.12
Weight incl. packaging	23.07
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	Yes
Battery connection	Clip
Dimming function	No
Luminous flux mains	- lm
Luminous flux emergency	900 lm
Customs tariff number	94054239
GTIN	4262483025987



TECHNICAL DRAWING



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
SGS1308WL		Wireless Professional (WL)	Single battery	RAL 7035	€€	yes	low	yes	1,000 per system	central

As of: 06.12.2025 - Subject to technical changes and errors.