



Art.-Nr: SKS2301SC

Safety luminaire Single Battery

Wall mounting, SelfControl (SC), 1 h, , IP54, Metal, Light grey

Compact emergency floodlight equipped with two freely adjustable metal safety luminaires. Suited to use indoors and, subject to certain conditions, to use outdoors.

Automatic monitoring of safety luminaire with SelfControl.



More information

www.rp-group.com/en/item/SKS2301SC



TECHNICAL DATA


Luminaire type	Safety luminaire
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Metal
Housing color	Light grey
Protection type (IP)	IP54
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	1
Supply	Single Battery
Monitoring	SelfControl (SC)
Bridging time	1 h
Battery	AGM - OGIV 12V 12 V/12,8Ah Ah
Operating mode	Standby circuit
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	12 V
Power max.	11,5 W
Power DS	- W
Power BS	9,2 W
Ambient temperature DS	-5 °C - 40 °C



Ambient temperature BS	-5 °C - 40 °C
Depth	120 mm
Width	300 mm
Height	300 mm
Weight	14.67
Weight incl. packaging	14.67
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	Clip
Dimming function	No
Luminous flux mains	- lm
Luminous flux emergency	2 x 2500 lm
Customs tariff number	94054239



TECHNICAL DRAWING



RELATED PRODUCTS

Art.-No.	Image	Monitoring	Supply	Color	Investment	Automatic log	Maintenance level	Remote maintenance	max. luminaires	Single luminaire monitoring
SKS2301WL		Wireless Professional (WL)	Single battery	RAL 7035	€€	yes	low	yes	1,000 per system	central

As of: 11.10.2024 - Subject to technical changes and errors.