



Art.-Nr: U6E019

Exit sign Centralised power supply systems

Recessed wall mounting, CPS, CPS, 22 m, IP40, Metal, white

Integrated into the wall this escape route indication luminaire adapts to the interior design. The variable use and toolless use of the pictograms provide planning security on site. LED escape route luminaire for recessed wall mounting to DIN EN 60598-1, EN 60598-2-22, EN 7010 and DIN EN 1838th.



More information




TECHNICAL DATA

Luminaire type	Exit sign
Mounting	Recessed wall mounting
Recognition distance	22 m
Pictograph	Set
Illuminant	LED
Housing material	Metal
Housing color	white
Protection type (IP)	IP40
Impact resistance (IK)	≥ 3
Certification	WEEE, CE
Insulation class	1
Supply	Centralised power supply systems
Monitoring	CPS
Bridging time	CPS
Operating mode	Permanent circuit
Input voltageAC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	100-254 V
Power max.	4,5 W
Power DS	4,5 W
Power BS	0 W
Depth	65 mm
Width	280 mm



Height	160 mm
Installation length	239 mm
Installation width	128 mm
Installation height	65 mm
Weight	1.05
Weight incl. packaging	1.32
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	300 lm
Luminous flux emergency	300 lm
Customs tariff number	94056180
Country of origin	DEUTSCHLAND
EAN	4260123687830

TECHNICAL DRAWING





ACCESSORY LIST

U6BE -

As of: 09.07.2024 - Subject to technical changes and errors.