



Art.-Nr: WAF029

**Safety luminaire Centralised power supply systems
Wall mounting, Without monitoring, CPS, , IP20, Zinc die-cast,
white**

High-grade zinc die-cast safety luminaire for surface mounting on the wall.

The radiating characteristics run parallel to the wall to help perfectly illuminate escape and emergency routes.



More information

www.rp-group.com/en/item/WAF029



TECHNICAL DATA


Luminaire type	Safety luminaire
Mounting	Wall mounting
Pictograph	No
Illuminant	LED
Housing material	Zinc die-cast
Housing color	white
Protection type (IP)	IP20
Impact resistance (IK)	4
Certification	WEEE, CE
Insulation class	2
Supply	Centralised power supply systems
Monitoring	Without monitoring
Bridging time	CPS
Battery	/
Operating mode	Permanent circuit
Input voltage AC	230 V
Input frequency	50 / 60 Hz
Input voltage DC	100-254 V
Power max.	3,9 W
Power DS	3,9 W
Power BS	0 W
Ambient temperature DS	-25 °C - 35 °C



Ambient temperature BS	-25 °C - 40 °C
Depth	193 mm
Width	53 mm
Height	115 mm
Weight	0.04
Weight incl. packaging	0.07
Connection cross-section	1.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	420 lm
Luminous flux emergency	420 lm
Customs tariff number	94056180
EAN	4260581710941



TECHNICAL DRAWING



As of: 11.10.2024 - Subject to technical changes and errors.