



Art.-Nr: XGIU009ML

Safety luminaire Central power supply

Universal, ML, Central power supply, , IP66, Aluminum die-cast, Glass, Housing color

Explosion-proof LED glass cylinder Safety light for gas and dust Ex zones.

Available in three sizes with a luminous flux of up to 5000lm.

Prepared for two cable entries for through-wiring. By applying a pictogram can also be used as a exit sign.

Mounting options Wall or ceiling mounting with adapter or suspension with chain eye.

According to 2014/34/EG (ATEX)

Zone 1 / Zone 21 gas and dust

- Ex d IIB T6 Gb / Ex d IIB T6 Gb

- Ex t IIIC T85°C Db

Built according to:

-EN 60079-0:2018, EN 60079-1:2014, EN 60079-31:2014

-Certified by INERIS 20ATEX0005X



More information



TECHNICAL DATA


Luminaire type	Safety luminaire
Mounting	Universal
Pictograph	No
Illuminant	LED
Housing material	Aluminum die-cast, Glass
Protection type (IP)	IP66
Impact resistance (IK)	7
Certification	Waste disposal, CE
Insulation class	1
Supply	Central power supply
Monitoring	ML
Bridging time	Central power supply
Operating mode	Permanent circuit
Input voltageAC	230 V



Input frequency	50 / 60 Hz
Power max.	11 W
Power DS	11 W
Power BS	1,5 W
Depth	485 mm
Width	157 mm
Height	197 mm
Weight	4.28
Weight incl. packaging	4.78
Connection cross-section	2.5 mm ²
Switching input	No
Emergency light blocking	No
Battery connection	No
Dimming function	No
Luminous flux mains	1200 lm
Luminous flux emergency	1200 lm
Customs tariff number	94051190
Country of origin	SPANIEN
EAN	4260682145390



TECHNICAL DRAWING



ACCESSORY LIST

- X-KE001 -
- X-KO001 -
- X-MB001 -
- X4N -

As of: 29.06.2024 - Subject to technical changes and errors.